



GEAR HOBBING CENTER

- 8 axis CNC
- Max. module **1.5 mm / 17 DP**
- Max. cutting length 90 mm / 3.54 in.
- Max. part diameter 60 mm / 2.36 in.
- Gear Process Worm Screw Power Skiving



Technical characteristics

Max. part diameter

Max. part length clamping between drive centers

Max. cutting length clamping between drive centers

Max. part length clamping between collet and tailstock

Max. cutting length clamping between collet and tailstock _

Max. module (depending on material and process)_

Max. diameter of the hob cutter _

Max. width of the hob cutter _

Inclination of the cutting spindle _

Max. spindles rotation ___

Dimensions (LxWxH)

www.affoltergroup.ch

* According to the setup and the quality required. | ** According to clamping of tools. | *** Option.

100 mm / 3.94 in. 50 mm / 1.97 in.** 200 mm / 7.87 in. 90 mm / 3.54 in.** 1.5 mm / 17 DP 38 mm / 1.496 in. 50 mm / 1.97 in. +/- 30° 12'000 rpm *** 1180x1660x2589 mm 1505 kg / 3318 lbs

60 mm / 2.36 in.*



The programing is simple and user-friendly.

The machine comes with a 12" color touch-screen monitor. There is a possibility to network the machines and download the programs on a PC or a server.

Automation and option

The AF110 plus offers a variety of automation solutions to be adapted to any application, ranging from flexible manufacturing of small series up to heigh volume production with an autonomy of 12 to 24 hours:

- AF45 and AF71 loaders with vibratory bowl feeder, magazine, and many different conveyor options.
 - Customizable coolant systems, oil, oilmist, coolant.
 - Option: chip extraction conveyor with filtration, collet clamping, dry cutting, skiving, deburring and Worm Screw Power Skiving







